



Anti-Adhesive Free Silicone Agent (I251)

It is the perfect spray to prep printed materials (plastics, paper, rubber.). Ideal for plastic and rubber moldings in general. It doesn't leave residuals, and does not create foreign bodies. It posses lubricating and detaching power. What more do you want?



Quantity	400 ml
Barcode	EAN 13: 8034108890265
Box / Case	12 pz

ANTI-ADHESIVE FREE SILICONE AGENT - Suitable for manufacturing, screen printing, and paper industry. Ideal for plastic and rubber molding in general. It permits plastic products to be painted, printed, glued or sealed without problem. The product also provides good lubricant and detaching properties suited for the printing, papering and binding sectors. It promotes the smooth sliding of paper, it does not affect the adhesion of rubber and it does not create residue/deposits.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	yellow
Odour	Characteristic of solvent
Relative density	at 20°C 0,61 ÷ 0,65 g/ml
Flash point	Und.0° C extremely flammable
Pressure at 20°C	4/6 bar
Vapour pressure	< 0,01 hPa a 20°C (dry residue)
Vapour density	9-12 (dry residue) (air = 1)
Viscosity at 50°	(ASTM D 445) 11 ÷ 24 cst (dry residue)
Solubility	Insoluble in water

HOW TO USE: Clean well the surface to be treated, eliminating dirt or residuals. Apply uniformly from a distance of around 20-30cm.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT