



Stringy permanent multipurpose glue (I254/FIL)

A spray can that is actually a real portent! Almost immediate drying, usable on the most varied materials, resistant to high temperatures... We have revealed the main secrets, now you just have to try it!

STRINGY PERMANENT MULTIPURPOSE GLUE – It has high performance: particularly suitable for gluing rubber, metal, vinyl materials, fabrics, wood, paper, plastics in general. It has a resistance to heat even when subjected to prolonged exposure. It also resists very well to plasticizers in general. Product equipped with adjustable button.

Technical Specifications:

Aspect	Cylinder containing liquid under pressure
Color	Colourless
Smell	Solvent characteristic
Relative density	at 20°C 0,73 ÷ 0,77 Kg/L
Flash point	Inf. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Dry residue	43 - 45 %
Viscosity at 20°C	400 - 600 mPa·s. (Brookfield viscometer RVT).
Tack (stickiness)	Very strong
Grip	Rapid
Drying	Min. 2' – Max 4'

HOW TO USE: Shake well before use. Clean the part to be glued. Spray the product on one of the surfaces to be glued. Overlap the other adhering to the glued part exerting strong pressure. The initial setting is quick but complete adhesion occurs within 24 hours.

STORAGE METHODS

Before use: Store the product in a dry place and do not store it at temperatures below 5 ° C and above 35 ° C, after use keep the containers tightly closed. If stored in the original packaging, the product can be stored for 24 months (warranty). The product does not expire.

After first use: Store in a cool, dry place, away from heat sources. Keep out of reach of children.

This information, although considered reliable, must be considered indicative. Their use does not imply any liability on our part, including infringement of any patents or licenses. It is the responsibility of users to verify in advance the suitability of the product for the specific use.

CONSULT THE PRODUCT SAFETY DATA SHEET BEFORE USE