



Multifunctions Unblocking 5 Lt (S155)

This unlocking and protective fluid is contained in a bigger size too. It can be used on mechanical parts, it protects from humidity and fire and also removes rust and oxidations.



Quantity	5 Lt
Barcode	EAN 13: 8034108891644
Pack	1 pz

UNBLOCKING – A penetrating synthetic fluid with a high solvent and releasing power. It supports the releasing process of bolts, joints, threads, hinges and all other mechanical parts from rust and oxidation. It also leaves a long lasting waterproof and water repellent protective film.

Technical Specifications:

Aspect	Tank
Color	Straw yellow
Odour	Characteristic of solvent
Relative density	at 20°C 0,80 ÷ 0,84 g/ml
Flash point	>60 °C flammable
Melting/freezing point	-52°C ~
Vapor tension	0,5 hPa (20°C)
Viscosity	> 9 cSt 40°C
Solubility	Insoluble in water
Operating temperature	-50°C / +130 °C c.a.
Ignition temperature	>200 °C
Boiling temperature	+160 / +245 °C
Boiling point	>170 °C

HOW TO USE: application with brush or spray. Apply the product on the surface to be treated, leave for a few minutes, then in the case of rusted parts proceed to unlock. With resistant rust repeat the operation. The product is ready to use. To further dilute the product use white spirit/naphta hydrotreating

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 35°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT