



Gas Leaks Detector (W507)

Gas breaks are dreaded, and also really dangerous. For that, Ambro-Sol offers this practical and simple spray: it can be used on tubes, valves, connections, tanks. It is a non-flammable product, so it can be used on machinery and flammable conductors.

GAS LEAKS DETECTOR – A product with synthetic active agents which can detect leaks of gas or compressed air in pipes, valves, connections, canisters and pressurized tanks. It is non-flammable, so it can be used to check on gas stoves and mains.



Technical Specifications:

Barcode	EAN: 8034108890524
Quantity	400 ml
Box / Case	12 Pz.
Aspect	Tin-Plate can containing under pressure fluid
Color	Colorless
Odour	odorless
Relative density	at 20°C 0.96 ÷ 1,00 g/ml
Flash point	Not flammable
Pressure at 20°C	7 bar +/-
Operating temperature	>0°C/100°C
PH	7,5-8,5
Boiling range	>100°C
Decomposing temperature	>200°C
Solubility	Water soluble
Biodegradability	92% (H2O compound)
Gas	Nitrogen

HOW TO USE: Shake well before use. Hold the bottle upright and spray from a distance of 20-25 cm on the area to be tested. In case of leak, bubbles or foam will form. The product can also be used with the attached straw (multi-straw cap). Protect from frost.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT